

Data Sheet

BLEEDER LEASE® G

Coated polyester peel ply

DESCRIPTION

Bleeder Lease® G peel ply is a high temperature fabric coated with a silicone release agent. Bleeder Lease® G provides superior release to plain peel plies because the coating prevents the heated fabric from fusing to the laminate while producing a textured surface. Bleeder Lease® G material will provide easy release from most prepregs and resin systems. All coated peel plies have the potential to transfer. Bleeder Lease® G is a tightly woven coated polyester material that will release from the more difficult resin systems. The polyester adds strength, making removal easier.

TECHNICAL DATA

Maximum use temperature	400 °F (204 °C)
Fiber type	Polyester
Fabric construction: warp x fill	120 x 64 ends/in x picks/in (472 x 252 ends/ dm x picks/ dm)
Weight	2.45 oz/yd ² (83 g/m ²)
Thickness	0.005 inch (0.13 mm)
Color	Green
Coating type	Silicone
Shelf life	Unlimited

SIZES

Width	Length	Packaging
60 inches (152.4 cm)	100 yards (91 m)	1 roll

NOTES

- > Maximum use temperature is dependent upon the duration at maximum temperature and is process specific. Airtech recommends testing prior to use.
- > Hot knife slitting upon request with 1 roll as minimum order quantity.