5700 Skylab Road Huntington Beach CA 92647 USA Phone: +1 714-899-8100 Fax: +1 714-899-8179 E-mail: airtech@airtechintl.com Website: www.airtechonline.com

### **Data Sheet**

# **ECONOSTITCH G**

## Polyester peel ply with black tracers

#### DESCRIPTION

Econostitch G is an economical, heat set and scoured peel ply with good performance when used with both polyester and epoxy resins. Econostitch G has black tracers with high visibility to reduce the risk of peel ply being left on the part.

Our Econo peel plies are designed to work in resin infusion or hand lay-up processes. Econostitch eliminates the need for sanding or abrading on your composite laminate.

#### TECHNICAL DATA

Maximum use temperature 375 °F (190 °C) Fiber type Polyester

Weight  $2.5 \text{ oz/yd}^2 (85 \text{ g/m}^2)$  Thickness 0.005 inch (0.13 mm)

Color White Tracer Black

Extractables <0.5% % by weight

Shelf life Unlimited

#### SIZES

Width	Length	Packaging
71 inches (180 cm)	218 yards (200 m)	1 roll

#### NOTES

> Maximum use temperature is dependent upon the duration at maximum temperature and is process specific. Airtech recommends testing prior to use.

> Hot knife slitting upon request with 1 roll as minimum order quantity.

Last updated: 2014-09-12

Catalog position: Release fabrics / Peel plies